Building/Year built: Skypark/Rec Center Team: Dana Esposito and Shelley Zuniga

Date: 11/10/2015 Job#: R15025

## MULTIPLE DOORS CHECKLIST

Cite:	Question:	Door: E	Door: I	Door: I	Door: I	Door: I	Door: I	Door: E	Door: I	Door: E
		Door #:	Door #:	Door #:	Door #:	Door #:	Door #:	Door #:	Door #:	Door #:
		Main	Staff	public	file storage	break to	storage to	Break exit	Division	division
		entrance	restroom	restroom		storage	rec room		manager	manager exit
	If a double door, measure	only the act	ive leaf							
404.2.4	Maneuvering clr.	Yes	Storage	Yes	No, interior	Storage	No,	No,	No, chair	No, shelf
404.2.4.1	around doors/entries		on pull		storage	on pull	storage on	narrow	on pull	on push
404.2.4.2			( <u>SP3</u> )		and small	(SP6)	pull (SP27)	pad; 10"	(SP12)	( <u>SP13</u> )
			,		( <u>SP5</u> )	,		on pull	,	,
					( <u>===</u> )			(SP7, SP8)		
404.2.4.4	Do floor surfaces in MC	Yes	n/a	n/a	n/a	n/a	n/a	2.2%	n/a	2.3%
	comply with 302 (slope,							( <u>SP10</u> ,		(SP14,
	CIL, gaps)?							<u>SP11</u> )		SP15)
307.4	80" Head Clearance	Yes	Yes	Yes	Yes	Yes	Yes	Yes	n/a	Yes
	(excl. closer; min 78")									
404.2.3	Door width 32"; with no	Yes	Yes	Yes	25.5" ( <u>SP4</u> )	Yes	Yes	Yes	Yes	Yes
	projections > 4"									
	between 34" and 80"?	,		,	,	,		,	,	
404.2.3	If door is 24" D, is it 36" W	n/a	n/a	n/a	n/a	n/a	Yes	n/a	n/a	n/a
303.2	Change in level < 1/4"	n/a	Yes	Yes	n/a	n/a	Yes	1.75"	n/a	2.25"
								( <u>SP9</u> )		( <u>SP16</u> )
404.2.5	Thresholds < ½ "	1" ( <u>SP1</u> )	Yes	Yes	n/a	n/a	n/a	Yes	n/a	Yes
404.2.5	If existing threshold is	No 1"	Yes	Yes	n/a	n/a	n/a	n/a	n/a	Yes
	3/4" is it beveled at 1:2?									
	(exception)									
302.2	If carpeted is pile < ½"	Yes	n/a	n/a	n/a	n/a	n/a	n/a	No, carpet	Yes
									fraying	
									( <u>SP207</u> ,	
									<u>SP208</u> )	
302.3	If openings in floor,	n/a	Yes	Yes	n/a	n/a	Yes	n/a	n/a	n/a
	<1/2" and perpendicular									
309.4;	Door hardware	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Date: 11/10/2015

Team: Dana Esposito and Shelley Zuniga

2							roperty of Recr	oation Accor	cibility Cond	sultants IIC
404.2.6	Series of doors clearance (48" clear width, doors	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
404.2.8.2	For spring hinges – closer 1.5 sec. from 70 to close	n/a	n/a	n/a	n/a	n/a	n/a	n/a	N/a	n/a
104.2.11	Do doors w/side lights for view have at least one panel max 43" aff? (exc. if bottom above 66")	Yes	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
104.2.10	Is the surface of the door from floor to 10" aff on the push side smooth or have a kick plate? (horizontal gap 1/16" max)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
104.2.8	Door closers: 3 sec. from 70 to 3"	Yes	No	No	n/a	n/a	No, fast	n/a	n/a	No, fast
11B- 104.2.9	Exterior doors pull force (5 lbf) or 8.5 lbf if power doors exist	6#	n/a	n/a	n/a	n/a	n/a	n/a- broken	n/a	9#
104.2.9	Pull Force; int. hinged doors; sliding or folding doors (5 lbf)	n/a	Yes	Yes	n/a	n/a	6#	n/a	n/a	n/a
11B- 404.3.5	Do power doors have two push plates, one at 7"-8" aff and the other 30"-44" aff?	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
104.3.5	Is the CFS at the power door controls located outside of any door swing?	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
L1B- 104.2.7	Hardware height (34"- 44")	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
imart oractice	Hazardous areas knurled handle	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
404.2.7	compliant?									

Building/Year built: Skypark/Rec Center Team: Dana Esposito and Shelley Zuniga

Date: 11/10/2015 Job#: R15025

	open)									
404.2.7	Sliding doors hardware usable without tight pinch or grasp and on both sides?	n/a								
Other:										

Rev. 04/21/14

Cite:	Question:	Door: I Door #: School-aged office	Door: I Door #: storage in hall	Door: I Door #: Sports office	Door: I Door #: Rec by entrance	Door: E Door #: Exit to parking in rec	Door: I/E Door #: Exit to park in rec	Door: E Door #: Right storage shed	Door: E Door #: Center storage shed	Door: E Door #: Left storage shed
	If a double door, measure	only the activ	e leaf			•				
404.2.4 404.2.4.1 404.2.4.2	Maneuvering clr. around doors/entries	No, table on pull (SP210)	No entry (SP19)	No, counter and storage on pull (SP215)	Yes	No, 6" to edge of cement (SP21)	Yes	No, storage ( <u>SP28</u> )	Yes	No, storage ( <u>SP45</u> )
404.2.4.4	Do floor surfaces in MC comply with 302 (slope, CIL, gaps)?	Yes	Yes	Yes	Yes	Yes	8.3% ( <u>SP25</u> , <u>SP26</u> )	3.8% ( <u>SP29</u> , <u>SP30</u> )	9.7% ( <u>SP36</u> , <u>SP37</u> )	9.2% ( <u>SP40</u> , <u>SP41</u> )
307.4	80" Head Clearance (excl. closer; min 78")	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
404.2.3	Door width 32"; with no projections > 4" between 34" and 80"?	Yes	22" ( <u>SP18</u> )	Yes	Yes	Yes	Yes	Yes	Yes	Yes
404.2.3	If door is 24" D, is it 36" W	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
303.2	Change in level < 1/4"	n/a	n/a"	n/a	Yes	2.25" ( <u>SP23</u> )	Yes	2.5" ( <u>SP31</u> )	1" ( <u>SP38</u> )	3" ( <u>SP44</u> )

Date: 11/10/2015

Team: Dana Esposito and Shelley Zuniga

404.2.5	Thresholds < ½ "	n/a	n/a	n/a	Yes	Yes	Yes	n/a	n/a	n/a
404.2.5	If existing threshold is 3/4" is it beveled at 1:2? (exception)	n/a	n/a	n/a	Yes	Yes	Yes	n/a	n/a	n/a
302.2	If carpeted is pile < ½"	Yes	Yes	No, fraying	n/a	n/a	n/a	n/a	n/a	n/a
302.3	If openings in floor, <1/2" and perpendicular	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
309.4; 404.2.7	Door hardware compliant?	Yes	Yes	Yes	Knob ( <u>SP20</u> )	Yes	Yes	No, small ( <u>SP33</u> )	No, small	No, small
Smart practice	Hazardous areas knurled handle	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
11B- 404.2.7	Hardware height (34"- 44")	Yes	Yes	Yes	Yes	Yes	Yes	48" ( <u>SP34</u> )	45" ( <u>SP42</u> , SP43)	Yes
404.3.5	Is the CFS at the power door controls located outside of any door swing?	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
11B- 404.3.5	Do power doors have two push plates, one at 7"-8" aff and the other 30"-44" aff?	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
404.2.9	Pull Force; int. hinged doors; sliding or folding doors (5 lbf)	n/a	n/a	n/a	n/a-close broken	n/a	n/a	n/a	n/a	n/a
11B- 404.2.9	Exterior doors pull force (5 lbf) or 8.5 lbf if power doors exist	n/a	n/a	n/a	n/a	7#	n/a	n/a	n/a	n/a
404.2.8	Door closers: 3 sec. from 70 to 3"	n/a	n/a	n/a	n/a	No, fast	n/a	n/a	n/a	n/a
404.2.10	Is the surface of the door from floor to 10" aff on the push side smooth or have a kick plate? (horizontal gap 1/16" max)	n/a	Yes	Yes	Yes	Yes	Yes	n/a	n/a	n/a

Date: 11/10/2015

Team: Dana Esposito and Shelley Zuniga

404.2.11	Do doors w/side lights for view have at least one panel max 43" aff? (exc. if bottom above 66")	n/a								
404.2.8.2	For spring hinges – closer 1.5 sec. from 70 to close	n/a								
404.2.6	Series of doors clearance (48" clear width, doors open)	n/a								
404.2.7	Sliding doors hardware usable without tight pinch or grasp and on both sides?	n/a								
Other:										

Cite:	Question:	Door: E	Door: E	Door: I/E						
		Door #:	Door #:	Door #:	Door #:	Door #:	Door #:	Door #:	Door #:	Door #:
		W park RR	M park RR							
	If a double door, measure	only the activ	e leaf							
404.2.4	Maneuvering clr.	No: 9.5"to	Yes							
404.2.4.1	around doors/entries	sink on								
404.2.4.2		push ( <u>SP179</u> )								
404.2.4.4	Do floor surfaces in MC comply with 302 (slope, CIL, gaps)?	Yes	Yes							
307.4	80" Head Clearance (excl. closer; min 78")	Yes	Yes							
404.2.3	Door width 32"; with no projections > 4" between 34" and 80"?	Yes	Yes							

Date: 11/10/2015

Team: Dana Esposito and Shelley Zuniga

404.2.3	If door is 24" D, is it 36" W	n/a	n/a				
303.2	Change in level < 1/4"	n/a	n/a				
404.2.5	Thresholds < ½ "	n/a	n/a				
404.2.5	If existing threshold is 3/4" is it beveled at 1:2? (exception)	n/a	n/a				
302.2	If carpeted is pile < ½"	n/a	n/a				
302.3	If openings in floor, <1/2" and perpendicular	n/a	n/a				
309.4; 404.2.7	Door hardware compliant?	Yes	Yes				
Smart practice	Hazardous areas knurled handle	n/a	n/a				
11B- 404.2.7	Hardware height (34"- 44")	Yes	Yes				
404.3.5	Is the CFS at the power door controls located outside of any door swing?	n/a	n/a				
11B- 404.3.5	Do power doors have two push plates, one at 7"-8" aff and the other 30"-44" aff?	n/a	n/a				
404.2.9	Pull Force; int. hinged doors; sliding or folding doors (5 lbf)	n/a	n/a				
11B- 404.2.9	Exterior doors pull force (5 lbf) or 8.5 lbf if power doors exist	No: 10#	No: 11#				
404.2.8	Door closers: 3 sec. from 70 to 3"	Yes	Yes				
404.2.10	Is the surface of the door from floor to 10" aff on the push side smooth or have a kick plate? (horizontal gap	Yes	Yes				

Date: 11/10/2015

Team: Dana Esposito and Shelley Zuniga

	1/16" max)						
404.2.11	Do doors w/side lights for view have at least one panel max 43" aff? (exc. if bottom above 66")	n/a	n/a				
404.2.8.2	For spring hinges – closer 1.5 sec. from 70 to close	n/a	n/a				
404.2.6	Series of doors clearance (48" clear width, doors open)	n/a	n/a				
404.2.7	Sliding doors hardware usable without tight pinch or grasp and on both sides?	n/a	n/a				
Other:							